



Приватне Підприємство
«КОМПАНІЯ САНРАЙЗ»

ЄДРПОУ 36372819
 Україна, м. Харків, вул. Ковтуна, 52

р/р 26005176272
 МФО 380805
 АТ «Райффайзен Банк Аваль» м. Харків

Тел.: +38 (067) 7318107
 Факс: +38 (067) 2369589
 @mail: office@selhozmash.com
 WWW: www.selhozmash.com

EXPELLER

Expellers are used for final pressure of oil from oilcake, which is obtained after having been pressed in a forepress. SUNRISE manufactures expellers that have the productivity of 200-600 kg/hour. The expellers we produce are made as a single-screw press having a vertical split-face loose pressing cage. The press is driven by a three-phase current motor through a cylindrical or planetary drive. The distributor already prepresses the raw material in the vertical input hole. It contributes to the complete optimal filling of a pressing cage. The feed screw provides the even regulated supply of raw materials into the press. The rapidly wearing parts of a horizontal press duct are armored. The screw shaft rests upon one or two points on the bed plate of a press.



| Characteristics | Unit measure | Oil press model | | |
|----------------------|--------------|----------------------|----------------------|----------------------|
| | | MPZEh-200 (мпзэ-200) | MPZEh-400 (мпзэ-400) | MPZEh-600 (мпзэ-600) |
| Productivity | kg/ hour | 100-200 | 200-400 | 400-800 |
| Power | kilowatt | 7.5-11 | 11-15 | 15 |
| Residual oil content | % | 4-7 | 4-7 | 4-7 |
| Dimensions | mm | 2265x690x890 | 2310x690x1100 | 3090x1280x1810 |