



Приватне Підприємство
«КОМПАНІЯ САНРАЙЗ»


ЄДРПОУ 36372819
 Україна, м. Харків, вул. Ковтуна,52

р/р 26005176272
 МФО 380805
 АТ «Райффайзен Банк Аваль» м. Харків

Тел.: +38 (067) 7318107
 Факс: +38 (067) 2369589
 @mail: office@selhozmash.com
 WWW: www.selhozmash.com

FOREPRESS

Forepresses are used for preliminary pressure of oil-yielding crops when using two-phase pressing. The company SUNRISE produces forepresses having productivity 100 - 3000 kg/hour. The forepresses are reliable in operation and can pressure oil without heating raw materials or under low temperature. The forepresses of cold pressing are single-screw presses having a vertical split-face loose pressing cage. The press is driven by a three-phase current motor through a cylindrical or planetary drive. The distributor already makes the prepressing of the raw material in the vertical input hole. It contributes to the complete optimal filling of a pressing cage. The horizontal feed screw provides the even regulated supply of raw materials into the press. The rapidly wearing parts of a horizontal press duct are armored. The screw shaft rests upon one or two points on the bed plate of a press.



Characteristics	Oil press model/td>			
	MPZ-200 (мпз-200)	MPZ-500 (мпз-500)	MPZ-1000 (мпз-1000)	MPZ-2000 (мпз-2000)
Productivity on seeds kg/hour	100-400	400-600	600-1500	1000-2000
Power kilowatt	11-15	15-18	18-22	22-30
Residual oil content in the mode of forepressing %	13-18	13-18	13-18	13-18
Residual oil content in the mode of final pressing %	6-9	6-9	6-9	6-9
Dimensions mm	2265x690x890	2310x690x1100	3090x1280x1810	3620x1280x1700